

WARNING!

VEHICLE DAMAGE WILL OCCUR
IF YOU DO NOT FOLLOW
THESE INSTRUCTIONS.

Due to tire size variations between manufacturers, be sure to try on your tire chains as soon as you purchase them. This assures you that when you need chains, they are the proper size for your tires. Snow tires may require a size larger than regular tires.

- *Tire chains can break in use.
- *STOP IMMEDIATELY & REPAIR a broken tire chain.
- *Continued travel with a broken tire chain can cause damage to vehicle.
- *Manufacturer WILL NOT BE RESPONSIBLE for vehicle damage. (see Warranty info)
- *Tire chains are designed for use as a traction device only. They are not to be used for any other purposes such as towing, lifting, etc.
- *DO NOT EXCEED 30KM/H. Accelerate slowly. *AVOID SPINNING WHEELS. The life of the chains will vary according to road conditions, driving speed, and individual driving habits. Remove tire chains when driving on bare pavements.
- *AVOID - LOCKING WHEELS WHEN BRAKING, DRIVING ON BARE PAVEMENT, HITTING CURBS, IMPROPER INSTALLATION, OR OTHER ACTIVITIES WHICH ACCELERATE CHAIN WEAR UNNECESSARILY.
- *CAUTION! Tire chains and cables improve traction but are not intended to be used when all safe stopping and starting requirements. Consequently, the user is cautioned and encouraged to use good judgement in their use.
- *Vehicle wheel well clearance for traction devices are the responsibility of the automobile manufacturer.
- *Chains are electro galvanized. They may corrode during usage, especially due to salt on the roads.
- *Maintain your chains by washing them in hot water and drying them after use.

LIMITED WARRANTY

These goods are warranted free from defects in workmanship and materials for 90 days from date of purchase.

DISCLAIMER OF WARRANTIES: NO WARRANTY, EXPRESS OR IMPLIED, INCLUDING THE IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR PARTICULAR PURPOSE, IS GIVEN AND NO AFFIRMATION OF SELLER, BY WORDS OR ACTION, SHALL CONSTITUTE A WARRANTY.

BUYERS REMEDIES:

Buyer's sole remedy for breach of any warranty is limited exclusively to obtaining, at the discretion of seller, either repair or replacement of any product sold here under and manufactured by seller. The seller will not pay any claim for labour on any of its products or for delays or damages by reason of their use. In no event shall Seller be liable for any incidental or consequential damages. Buyer must notify Seller, in writing, within 10 days of discovery of the alleged defect and within the warranty period stated above.

Direct correspondence by email to sales@qccanada.com or the address shown on this literature. After receiving authorization from Seller, product shall be returned to Seller's plant, transportation prepaid within 30 days.

STORAGE & CARE

Wash chains with clean water. Hang chains in a dry location. After chains are completely dry, spray with an anti-coating spray.



ATV GRIPPER CHAIN INSTALLATION INSTRUCTIONS

www.qccanada.com

1-888-507-9734

info@qccanada.com

IMPORTANT - "Damage will occur if you don't follow these instructions."

ATV GRIPPER CHAINS INSTALLATION INSTRUCTIONS


IMPORTANT - "Damage will occur if you don't follow these instructions."




1 Lay the chains on the ground. Spread out evenly and parallel in front of each of the vehicle wheels where the chain will be installed. Ensure the V-Bars are facing down.




2 Grasp the side chain closest to you and lift onto the tire. The V-Bars should now be facing up.




3 Drape the chain over the tire as shown.




4 Rotate the vehicle forwards onto the chain which places the connections at the back of the vehicle where more room is present.



5 On the inside, take your side chain and feed the fastener through the link. Not too tightly as you still need to hook up the center section.
Side Chain: Chain that runs along left and right sides of tire chain assembly.




6 Fold the fastener over and lock in place with the keeper link.




7 Hook up your outer side chain in the same manner as step 5 and 6.




8 Grasp your 2 rings & pull upwards. This will tighten your center pattern.
(Tip: You may want to rock the vehicle forwards and backwards to help)



9 Take the long tails and feed them through the rings and pull them out to the side chain.



10 Attach the tails to the side chains with the shackles provided. At this time try to tighten the side chain some more.
Inset: Tie up loose side chain with wire ties or plastic tie straps. (Not Included)



11 Install the supplied spider tensioner and spread the arms out evenly.
Inset: Make sure the hook ends are facing out.



12 ATV Gripper chain and spider tensioner installed correctly.
Drive the vehicle a few hundred meters, stop and re-tighten side chain and the center section as needed.

TOLL FREE: 1-888-507-9734
info@qccanada.com